



100V/80A N-Channel Advanced Power MOSFET


Features

- Fast switching
- Low RDS(on) & FOM
- Low Gate Charge

Applications

- High Frequency Switching
- Synchronous Rectification

BVDSS	100	V
ID	80	A
RDSON@VGS=10V	5.9	mΩ
RDSON@VGS=4.5V	8.2	mΩ



Order Information

Product	Package	Marking	Reel Size	Reel	Carton
PGD10N080	TO-252	PGD10N080	13inch	2500PCS	50000PCS

Absolute Maximum Ratings

Symbol	Parameter	Rating	Unit
Common Ratings (TC=25°C Unless Otherwise Noted)			
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	100	V
V_{GS}	Gate-Source Voltage	±20	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
I_S	Diode Continuous Forward Current	TC =25°C 80	A
Mounted on Large Heat Sink			
E_{AS}	Single Pulse Avalanche Energy (Note1)	210	mJ
I_{DM}	Pulse Drain Current Tested (Silicon Limit) (Note2)	TC =25°C 240	A
I_D	Continuous Drain current	TC =25°C 80	A
P_D	Maximum Power Dissipation	TC =25°C 110	W
$R_{θJC}$	Thermal Resistance Junction-to-Case (Note3)	1.14	°C/W

**100V/80A N-Channel Advanced Power MOSFET**

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T_J = 25°C (unless otherwise stated)						
V _{(BR)DSS}	Drain- Source Breakdown Voltage	VGS=0V ID=250μA	100	--	--	V
I _{DSS}	Zero Gate Voltage Drain current	VDS=80V,VGS=0V	--	--	1	μA
I _{GSS}	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
V _{GS(TH)}	Gate Threshold Voltage	VDS=VGS,ID=250μA	1	2	2.5	V
R _{DS(ON)}	Drain-Source On-State Resistance (Note4)	VGS=10V, ID=30A	--	5.9	7.7	mΩ
		VGS=4.5V, ID=20A	--	8.2	11.2	mΩ
Dynamic Electrical Characteristics @ T_J = 25°C (unless otherwise stated) (Note5)						
C _{iss}	Input Capacitance	VDS=50V, VGS=0V, F=1MHz	--	2760	--	pF
C _{oss}	Output Capacitance		--	679	--	pF
C _{rss}	Reverse Transfer Capacitance		--	30.5	--	pF
Q _g	Total Gate Charge	VDS=50V, ID=15A, VGS=10V	--	40.1	--	nC
Q _{gs}	Gate-Source Charge		--	6.7	--	nC
Q _{gd}	Gate-Drain Charge		--	8.5	--	nC
Switching Characteristics (Note5)						
t _{d(on)}	Turn-on Delay Time	VDS=50V, ID=15A, RG=6Ω, VGS=10V	--	14.3	--	nS
t _r	Turn-on Rise Time		--	28.7	--	nS
t _{d(off)}	Turn-off Delay Time		--	47.2	--	nS
t _f	Turn-off Fall Time		--	41.9	--	nS
Source- Drain Diode Characteristics @ T_J = 25°C (unless otherwise stated)						
V _{SD}	Forward on voltage	IS=20A,VGS=0V	--	--	1.2	V

Note:

- Limited by T_{Jmax}, starting T_J = 25° C, R_G = 25Ω, V_D =30V, V_{GS} =10V. Part not recommended for use above this value.
- Repetitive Rating: Pulse width limited by maximum junction temperature.
- Surface Mounted on FR4 Board, t ≤ 10 sec.
- Pulse Test: pulse width ≤ 300 us, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.



100V/80A N-Channel Advanced Power MOSFET

Typical Characteristics




Figure1: T_j Junction Temperature (°C)




Figure2: I_d Drain Current (A)




Figure3: T_j Junction Temperature (°C)




Figure4: V_{ds} Drain-Source Voltage (V)




Figure5: V_{ds} Drain-Source Voltage (V)




Figure6: Q_g Gate Charge (nC)



100V/80A N-Channel Advanced Power MOSFET




Figure7: Vsd Source-Drain Voltage (V)




Figure8: Vgs Gate-Source Voltage (V)




Figure9: Vds Drain-Source Voltage (V)




Figure10: Square Wave Pulse Duration (sec)

100V/80A N-Channel Advanced Power MOSFET

Test Circuit and Waveform:




Figure A Gate Charge Test Circuit & Waveforms




Figure B Switching Test Circuit & Waveforms





Figure C Unclamped Inductive Switching Circuit & Waveforms



100V/80A N-Channel Advanced Power MOSFET

TO-252 Package Outline Dimensions (Units: mm)



COMMON DIMENSIONS (UNITS OF MEASURE IS mm)			
	MIN	NORMAL	MAX
A1	0.000	0.100	0.150
A2	2.200	2.300	2.400
A3	1.020	1.070	1.120
b	0.710	0.760	0.810
c	0.460	0.508	0.550
D	6.500	6.600	6.700
D1	5.330REF		
D2	4.830REF		
E	9.900	10.100	10.300
E1	6.000	6.100	6.200
E2	5.600REF		
e	2.286TYPE		
L	1.400	1.550	1.700
L2	1.10REF		
L3	0.80REF		
L4	1.80REF		
θ	0~8°		
θ1	7° TYPE		
θ2	10° TYPE		
θ3	10° TYPE		